



1层钢丝编织增强, 1层纤维编织外覆的橡胶液压软管

SINGLE WIRE BRAID, TEXTILE COVERED HYDRAULIC RUBBER HOSE

- * **Application:** For delivery of petroleum base hydraulic fluids or water base liquids.
- * **Inner tube:** Seamless oil resistant synthetic rubber.
- * **Reinforcement:** 1 high tensile steel wire braid.
- * **Outer cover:** Oil, weather and abrasion resistant synthetic rubber covered by 1 impregnated textile braid.
- * **Temperature Range:** -40°C ~ +100°C (-40°F ~ +212°F)
- * **Fittings:** Reusable hose fittings 8 series with ferrule 00518 series.
- * **Specifications:**

产品型号 Part Number	规格 SIZE	内径 I.D	外径 O.D	工作压力 W.P		最小爆破压力 B.P		最小弯曲半径 Min Bend Radius	参考重量 Weight
				bar	psi	bar	psi		
P04-R5	3/16"	4.8	13.2	210	3045	840	12180	75	250
P05-R5	1/4"	6.4	14.8	210	3045	840	12180	85	290
P06-R5	5/16"	8	17.1	157	2277	628	9106	100	355
P08-R5	13/32"	10.3	19.4	140	2030	560	8120	115	410
P10-R5	1/2"	12.7	23.4	122	1770	488	7076	140	565
P12-R5	5/8"	16	27.4	105	1523	420	6090	165	700
P16-R5	7/8"	22.2	31.4	56	812	224	3248	185	695
P20-R5	1 1/8"	28.6	38.1	43	624	172	2494	230	920
P24-R5	1 3/8"	34.9	44.5	35	508	140	2030	265	1140
P32-R5	1 13/16"	46	56.4	24	348	96	1392	335	1375
P40-R5	2 3/8"	60	73	24	348	96	1392	610	2275
P48-R5	3"	76.2	90.5	14	203	56	812	840	3020

杭州派舜橡塑有限公司

HANGZHOU PAISHUN RUBBER & PLASTIC CO., LTD